

NextDent[™] 5100



NextDent 5100

| Build Volume (xyz) | 124.8 x 70.2 x 196 mm (4.9 x 2.8 x 7.7 in) | | |
|--|--|--|--|
| Max Resolution | 1920 x 1080 pixels | | |
| Pixel Pitch | 65 microns (0.0025 in) (390.8 effective PPI) | | |
| Wavelength | 405 nm | | |
| Build Materials | NextDent 5100 Dental Material Options: Materials specifications are listed on nextdent.com. For specific information about the available resins and colors for the NextDent 5100 please contact your authorized reseller or area sales manager. NextDent Denture 3D+, NextDent SG (Surgical Guide), NextDent Try-In, NextDent C&B MFH, | | |
| | NextDent Dentale 3D1, NextDent 3d (Sargical Guide), NextDent ITy-IT, NextDent Cab MirTi, NextDent Ortho IBT, NextDent Ortho Rigid, NextDent Model 2.0, NextDent Tray, NextDent Gingiva Mask, NextDent Cast | | |
| Material Packaging | 1kg bottles for manual pour | | |
| Operating Environment Temperature Humidity (RH) | 18-28 °C (64-82 °F) 20-80% | | |
| Electrical | 100-240 VAC, 50/60 Hz, Single Phase, 4.0A | | |
| Dimensions (WxDxH) 3D Printer crated Pedestal crated 3D Printer uncrated 3D Printer with Pedestal uncrated | 73.66 x 68.58 x 129.54 cm (29 x 27 x 51 in) 82.55 x 79.375 x 55.245 cm (32.5 x 31.25 x 21.75 in) 42.6 x 48.9 x 97.1 cm (16.7 x 19.25 x 38.22 in) 68.1 x 70.4 x 135.6 cm (26.8 x 27.71 x 53.38 in) | | |
| Weight 3D Printer crated Pedestal crated 3D Printer uncrated 3D Printer with Pedestal uncrated | 59 kg (130 lbs) 26.3 kg (58 lbs) 34.5 kg (76 lbs) 54.4 kg (120 lbs) | | |
| Production Time for Full Arch Model | 40 minutes to print a plate full of models | | |
| Accessories | LC-3DPrint Box UV post-curing unit (not included), Pedestal (not included), LC-3D Mixer (not included) | | |
| Certifications | FCC, CE, EMC | | |
| Warranty | 12 month manufacturer's warranty included. 12 to 24 month extended warranty options available. | | |
| | | | |





LC-3DPrint Box

| | · | חכ | N/A | ixer |
|---|-----|-----|-----|------|
| L | C - | 31) | IVI | ıxer |

| Related Voltage | 110/230 V, 50/60 Hz, 2.6/1.3 A | 100-240 V, 50/60 Hz |
|-------------------|--------------------------------|---------------------|
| Power consumption | 10 W | 10 W |
| Fuse | 250 V, T 2 A | 250 V, T 2 A |
| Dimension (WxLxH) | 41 x 44 x 38 cm | 410 x 270 x 100 mm |
| Weight | 22 kg | 4 kg |



www. 3 dsystems. com



Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.